


Product specification

Date:2021-10-07 Index: 1

Installation steps



Product: CP 130 gr

Description: Standard cellulose / polyester wall liner for indoor walls and ceilings.

Technical data:


Properties	Unit	Min value	Nom value	Max value
Width	mm	997	1000	1003
Length deviation	m	-0		
Thickness	mm		0,37	
Total weight	g / m ²		130	
<u>Tensile strength</u>				
MD	N / 5 cm	150	177	
CD	N / 5 cm	89	105	

Glue consumption See instructions on the glue bucket.

Paint consumption First coating Second coating
m² / litre 7,2 10,8

Facing side

Facing side is the outside of the roll.



Reverse side marking

No reverse side marking on this product.

Pattern matching

Free match





Allowed amount of marked spot faults

Roll length 15m Max 1
Roll length 25 & 30m Max 2
Roll length 50m Max 3

Note: A joint can occur in a roll and is considered as a spot fault.

Certificates:



Storing: -10 to +50 degrees Celcius
Use within 2 years after production

Information above is accurate to the best of our knowledge. Our products are subject to rigorous quality control along the production line to

ensure conformance. Divergence within our tolerance may occur.
Miksystems & Solutions AB Rundgängen 22 25452 Helsingborg +46728753771

